

**TIG Brush™**

POWERED BY ENSITECH

Always Leading

# TBE-440 TIG Brush™ Specifications

**Model Designation:** TIG Brush™ TBE-440**Market Location:** All regions except AUS/NZ

Feature	Details
Case Design	440 Series Injection Moulded IP65
Case Material	PC/ABS
Case Colour	Grey
Dimensions	245W x 190D x 370H
Weight (kg)	11kg
Mains Voltage	110/220 VAC +5%/-10%, single phase
Input Current	Average of 4 amps
Operating Environment	-30 °C to +45 °C (-22F to 113F)
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade (86F), on any Mode and Power setting.
Application Selection	Rotary Switch
Applications	Standby
	Single Brush 14V
	PROPEL™ / Wide 9V
Mode Selection	Rotary Switch
Modes Available	Clean
	Polish / Engrave
	Print
Power Supply	Dynamic Power Transfer - 300VA
Maximum Operating Output Current	60 amps
Overload Control	Smart Circuit
Cable Options	1: Classic Handle Cable & Wand
	2: Flexi-Handle
	3: PROPEL Torch
Cable Options	Black PVC insulated with Clamp
Maximum Brush size	Single
Standards Compliance	CE, C-Tick N22274

*Note: Ensitech reserves the right to update product specifications at any time without notice.*