

TIG Brush™

POWERED BY ENSITECH

Always Leading

TBE-700 TIG Brush™ Specifications

**Model Designation:** TIG Brush™ TBE-700**Market Location:** All regions except AUS/NZ

Feature	Details
Case Design	700 Series Injection Moulded IP65
Case Material	PC/ABS
Case Colour	Purple
Dimensions	245W x 190D x 370H
Weight (kg)	12kg
Mains Voltage	110/220 VAC +5%/-10%, single phase
Input Current	Average of 8 amps
Operating Environment	-30 °C to +45 °C (-22F to 113F)
Duty Cycle	Rated for continuous use at an ambient temperature of 30 degrees Centigrade (86F), on any Mode and Power setting.
Application Selection	Rotary Switch
Applications	Standby Single Brush 18V PROPEL™ / Wide: 13V
Mode Selection	Rotary Switch
Modes Available	Clean Polish / Engrave Print
Power Supply	Dynamic Power Transfer – 700VA
Maximum Operating Output Current	110 amps
Overload Control	Smart Circuit
Cable Options	1: Classic Handle Cable & Wand 2: Flexi-Handle 3: PROPEL Torch
Ground Cable	Black PVC insulated with Clamp
Maximum Brush size	Quad
Standards Compliance	CE, C-Tick N22274

Note: Ensitech reserves the right to update product specifications at any time without notice.